

STANDARD DRY BLOCK HEATER SPECIFICATIONS - 120 VOLT

	1 Block	2 Block	3 Block	4 Block	6 Block
Dimensions (L x W x H):	12.4 x 8 x 3.5" (31.5 x 20.3 x 8.9cm)	15.4 x 8 x 3.5" (39.1 x 20.3 x 8.9cm)	18.4 x 8 x 3.5" (46.7 x 20.3 x 8.9cm)	16.9 x 8 x 3.5" (42.9 x 20.3 x 8.9cm)	20.9 x 8 x 3.5" (53.1 x 20.3 x 8.9cm)
Electrical 120V 50/60 Hz:	0.9 amps, 110 watts	1.7 amps, 210 watts	1.7 amps, 210 watts	2.6 amps, 310 watts	3.4 amps, 410 watts
Fuses:	5mm x 20mm, 5 amp quick acting				
Temperature low range:	ambient +5°C to 100°C				
Temperature high range:	75°C to 150°C				
Stability @ 37°C:	+/-1°C	+/-1.5°C	+/-2°C	+/-2°C	+/-2°C
Uniformity w/in the block @ 37°C:	+/-0.1°C				
Uniformity across similar blocks @ 37°C:	N/A	+/-0.1°C	+/-0.15°C	+/-0.2°C	+/-0.3°C
Stability @ 60°C:	+/-3°C	+/-4°C	+/-4°C	+/-5°C	+/-5°C
Uniformity w/in the block @ 60°C:	+/-0.6°C				
Uniformity across similar blocks @ 60°C:	N/A	+/-0.8°C	+/-1°C	+/-1.2°C	+/-1.4°C
Heat-up time to 100 °C:	45 min.	50 min.	60 min.	70 min.	75 min.
Controls:	rocker switch heat indicator light low temperature knob, variable 1 to 10 dial markings high temperature knob, variable 1 to 10 dial markings				
Ship weight:	5.8lbs (2.6kg)	6.4lbs (2.9kg)	8lbs (3.6kg)	8.5lbs (3.9kg)	10lbs (4.5kg)