

## MODEL 3750

---

<b>Overall dimensions LxWxH</b>	16.25x14x5.75" (41.3x35.6x14.6cm)
<b>Tray dimensions LxW</b>	13x11" (33x22.2cm)
<b>Electrical</b>	120 volts, 5 amps, 40 watts 120 volts, 2.5 amps, 40 watts
<b>Fuses</b>	5mm x 20mm, 5 amp quick acting
<b>Speed Range</b>	20 to 300rpm
<b>Speed Accuracy</b>	
Above 100rpm	±1% of set speed
Below 100rpm	±1rpm
<b>Orbit</b>	0.75" (19mm) Total Travel
<b>Capacity</b>	~15 lbs @ 300rpm
<b>Timer</b>	1 second to 160 hours
<b>Controls</b>	See page 6
<b>Ship Weight</b>	49lbs (22.2kg)

## MODEL 5000

---

<b>Overall dimensions LxWxH</b>	23.6x26.7x6.0" (59.9x67.8x15.2cm)
<b>Tray dimensions LxW</b>	18x24" (45.7x70cm)
<b>Electrical</b>	120 volts, 5 amps, 75 watts 120 volts, 2.5 amps, 75 watts
<b>Fuses</b>	5mm x 20mm, 5 amp quick acting
<b>Speed Range (Advanced)</b>	20 to 500rpm
<b>(Standard)</b>	25 to 500rpm
<b>Speed Accuracy (Advanced)</b>	
Above 100rpm	±1% of set speed
Below 100rpm	±1rpm
<b>Orbit</b>	1" (25.4mm)
<b>Capacity</b>	~50 lbs @ 125rpm ~10 lbs @ 500rpm
<b>Timer (Advanced)</b>	1 second to 160 hours
<b>(Standard)</b>	1 to 120 minutes
<b>Controls (Advanced)</b>	See page 6
<b>(Standard)</b>	See page 5
<b>Ship Weight</b>	109lbs (49.4kg)

## MODEL 10000

---

<b>Overall dimensions LxWxH</b>	28.25x26.7x7.0" (71.8x67.8x17.8cm)
<b>Tray dimensions LxW</b>	24x24" (70x70cm)
<b>Electrical</b>	120 volts, 5 amps, 80 watts 120 volts, 2.5 amps, 80 watts
<b>Fuses</b>	5mm x 20mm, 5 amp quick acting
<b>Speed Range</b>	10000-1 = 15 to 500rpm 10000-2 = 15 to 300rpm
<b>Speed Accuracy</b>	
Above 100rpm	±1% of set speed
Below 100rpm	±1rpm
<b>Orbit</b>	15000-1 = 1" (25.4mm) 15000-2 = 2" (50.8mm)
<b>Capacity</b>	~100 lbs @ 100rpm ~40 lbs @ 300rpm
<b>Timer</b>	1 second to 160 hours
<b>Controls</b>	See page 6
<b>Ship Weight</b>	200lbs (90.7kg)

## MODEL 15000

---

<b>Overall dimensions LxWxH</b>	28.25x36x7.0" (71.8x67.8x17.8cm)
<b>Tray dimensions LxW</b>	24x36" (70x91.4cm)
<b>Electrical</b>	120 volts, 5 amps, 80 watts 120 volts, 2.5 amps, 80 watts
<b>Fuses</b>	5mm x 20mm, 5 amp quick acting
<b>Speed Range</b>	15000-1 = 15 to 350rpm 15000-2 = 15 to 300rpm
<b>Speed Accuracy</b>	
Above 100rpm	±1% of set speed
Below 100rpm	±1rpm
<b>Orbit</b>	15000-1 = 1" (25.4mm) 15000-2 = 2" (50.8mm)
<b>Capacity</b>	~150 lbs @ 100rpm ~40 lbs @ 300rpm
<b>Timer</b>	1 second to 160 hours
<b>Controls</b>	See page 6
<b>Ship Weight</b>	230lbs (104.3kg)