

Digital Models

Power requirements: 120VAC or 230 VAC, $\pm 10\%$, 50 or 60 Hz

Ambient conditions: . . . +4°C to +35°C, up to 75% relative humidity

Temperature range: Cover open: Ambient to 60°C; Cover closed:
Ambient to 100°C

Control: $\pm 0.1^\circ\text{C}$ between ambient and 100°C

Uniformity: $\pm 0.24^\circ\text{C}$ at 37°C

. $\pm 0.5^\circ\text{C}$ @ 37°C (Shallow Pan)

Stability: $\pm 0.5^\circ\text{C}$ at 37°C

*Max Altitude: 2000m

*Over Voltage Category II (IEC 664)

*Pollution Degree 2 (EC 664)

Analog Models

Power requirements: 120VAC or 230VAC, $\pm 10\%$, 50 or 60 Hz

Ambient conditions +4°C to +35°C, up to 75% relative humidity

Temperature range: Cover open: Ambient to 75°C, Cover closed:
Ambient to 100°C

Temperature range:

Model 18050AQ Cover open: Ambient to 85°C

Model 18020AQ . . . Cover open: Ambient to 70° C

Uniformity: $\pm 0.2^\circ\text{C}$ at 37°C

0.5°C at 37°C for Shallow Pan Units Only

Stability: $\pm 0.2^\circ\text{C}$ at 37°C

*Max Altitude: 2000m

*Over Voltage Category II (IEC 664)

*Pollution Degree 2 (IEC 664)

*

CE Products meet the relevant EC harmonized standards for safety (IEC1010-1/EN61010 and EMC (EN55014, EN55104, EN61000-4-2, -4-4, -4-6, -4-11 and ENV50140

*Applies to 230V units only