

## Specifications

---

These manufacturer's specifications should be used as guidelines when establishing your own performance specification.

Model	Volume μL	Increment μL	Accuracy		Precision	
			%	μL (±)	%	μL (≤)
L8-10, L12-10 (range 0.5-10 μL)	1	0.02	2.5	0.025	1.2	0.012
	5		1.5	0.075	0.6	0.03
	10		1.0	0.10	0.4	0.04
L8-20, L12-20 L2X8-20, L24-20 (range 2-20 μL)	2	0.02	7.5	0.15	2.0	0.04
	10		1.5	0.15	0.5	0.05
	20		1.0	0.20	0.3	0.06
L8-50, L12-50 (range 5-50 μL)	5	0.05	3.5	0.18	1.5	0.075
	25		1.2	0.30	0.4	0.1
	50		0.8	0.40	0.2	0.1
L2X8-100, L24-100 (range 10-100 μL)	10	0.2	3.5	0.35	1.0	0.1
	50		0.8	0.4	0.24	0.12
	100		0.8	0.8	0.15	0.15
L8-200, L12-200 (range 20-200 μL)	20	0.2	2.5	0.5	1.0	0.2
	100		0.8	0.8	0.25	0.25
	200		0.8	1.6	0.15	0.3
L8-300, L12-300 (range 20-300 μL)	30	0.5	2.5	0.75	1.0	0.3
	150		0.8	1.2	0.25	0.375
	300		0.8	2.4	0.15	0.45
L8-1200 (range 100-1200 μL)	100	2.0	3.6	3.6	0.60	0.60
	600		0.8	4.8	0.20	1.20
	1200		0.8	9.6	0.15	1.80

(Specifications subject to change without notice)

## Service

---

If you experience any problems with your multichannel Pipet-Lite, contact RAININ Technical Support at 800-543-4030.

E-mail: [tech.support@rainin.com](mailto:tech.support@rainin.com)

---

Rainin is a registered trademark and LTS, Lite-Touch System, and Pipet-Lite, are trademarks of Rainin Instrument, LLC. Pipet-Lite pipettes are manufactured under U.S. Patents 5,614,153, 5,700,959, and 5,849,248. LTS LiteTouch Tip Ejection System is protected under U.S. patents 6,168,761 B1 and 6,171,553 B1. Other U.S. and national patents pending.