

SPECIFICATIONS

POWER REQUIREMENTS:

Model 4631: 120 VAC, 50/60 Hz, 0.4 Amps, 50 Watts
Model 4631JPN: 100 VAC, 50/60 Hz, 0.5 Amps, 50 Watts
Model 4631-1(CE): 240 VAC, 50/60 Hz, 0.2 Amps, 50 Watts

SHAKER MOTION: A bi-directional movement, a horizontal and vertical orbital rotation through a 6° angle.

SHAKER SPEED: 0 to 25 revolutions-per-minute.

PLATFORM DIMENSIONS: 16" W x 14"D (41 x 36 cm)
13-1/8"W x 10"D x 4-3/16"H (33 x 25 x 11 cm)

NET WEIGHT: 14 lbs. (6 kg)

UNIT'S ENVIRONMENTAL OPERATING CONDITIONS:

POLLUTION DEGREE: 2
INSTALLATION CATEGORY: II
ALTITUDE: 2000 Meters MSL (Mean Sea Level)
HUMIDITY: 80% maximum, non-condensing
ELECTRICAL SUPPLY: 120VAC or 240VAC
VOLTAGE TOLERANCE: ±10% of normal rated line
TEMPERATURE: 15°C to 40°C
PRODUCT USAGE: This product is intended for use indoors **only**

SECTION 4

INSTALLATION