
General Specifications

Overall Dimensions (w x h x d):	9.625" (24.4 cm) x 4.25" (10.8 cm) x 10.75 (27.3 cm)
Platform Working Dimensions:	8.75" (22.2 cm) x .156" x 8.75" (22.2 cm)
Orbital Diameter:	0.80"
RPM (No Load Condition):	60 ± 5 RPM to at least 225 RPM
Maximum Load:	5 lbs. (2.3 kg)
Timer Range:	0-15 min.
Timer Accuracy:	±10 sec.

Environmental Conditions

Operating: 4°C -56°C; 20% to 80% relative humidity, non-condensing. Installation Category II (overvoltage) in accordance with IEC 664. Pollution Degree 2 in accordance with IEC 664.

Altitude limit: 2,000 meters.

Storage: -40°C to 70°C; 10% to 90% relative humidity.

Declaration of Conformity (-33 models only)

Barnstead|Thermolyne hereby declares under its sole responsibility that this product conforms with the technical requirements of the following standards:

EMC: EN 50081-1 Generic Emission Standard; EN 50082-1 Generic Immunity Standard;

Safety: IEC 1010-1-92 Safety requirements for electrical equipment for measurement, control, and laboratory use; Part I: General Requirements per the provisions of the Electromagnetic Compatibility Directive 89/336/EEC, as amended by 92/31/EEC and 93/68/EEC, and per the provisions of the Low Voltage Directive 73/23/EEC, as amended by 93/68/EEC.

The authorized representative located within the European Community is:

European Manager
Barnstead|Thermolyne
Saarbrückener Str. 248
D-38116 Braunschweig
Germany

Copies of the Declaration of Conformity are available upon request.