

INCUBATING ROCKING SHAKER SPECIFICATIONS

Overall dimensions (L x W x H):	17 x 11 x 10.5" (43.2 x 27.9 x 26.7cm)
Interior dimensions (L x W x H):	10.75 x 7.75 x 3.8" (27.3 x 19.7 x 9.7cm)
Tray dimensions (L x W):	10 x 7.5" (25.4 x 19.1cm)
Electrical (50/60 Hz):	120 volts AC, 5 amps, 450 watts 230 volts AC, 5 amps, 450 watts
Fuses:	5mm x 20mm, 5 amp quick acting
Temperature range:	ambient +5° to 65°C
Temperature uniformity:	±0.5°C at 37°C
Speed range:	1 to 50rpm *
Speed accuracy:	±1rpm
Tilt angle:	0 to 15° *
Timer:	1 second to 9999 minutes (increased in 1 second increments)
Maximum weight capacity:	10lbs (4.5kg) **
Controls:	see page 4
Tray material:	aluminum
Ship weight:	22lbs (10kg)

* Maximum speed/tilt angle may vary with heavy or unbalanced loads.

** Centered on tray.

INCUBATING WAVING SHAKER SPECIFICATIONS

Overall dimensions (L x W x H):	17 x 11 x 10.5" (43.2 x 27.9 x 26.7cm)
Interior dimensions (L x W x H):	10.75 x 7.75 x 3.4" (27.3 x 19.7 x 8.6cm)
Tray dimensions (L x W):	9.25 x 7.25" (23.5 x 18.4cm)
Electrical (50/60 Hz):	120 volts AC, 5 amps, 450 watts 230 volts AC, 5 amps, 450 watts
Fuses:	5mm x 20mm, 5 amp quick acting
Temperature range:	ambient +5° to 65°C
Temperature uniformity:	±0.5°C at 37°C
Speed range:	1 to 30rpm *
Speed accuracy:	±1rpm
Tilt angle:	0 to 20° *
Timer:	1 second to 9999 minutes (increased in 1 second increments)
Maximum weight capacity:	5lbs (2.3kg) **
Controls:	see page 4
Tray material:	aluminum
Ship weight:	22lbs (10kg)

* Maximum speed/tilt angle may vary with heavy or unbalanced loads.

** Centered on tray.