Hei-VAP Core - hand lift model with coated G5 dry ice condenser P/N: 036040058



An operating concept that is focused on the essentials: clear and with access to the basic parameters rotation speed and heating bath temperature at any time.

- Clear digital display showing actual and set values
- Two separate knobs with dynamic control for setting the rotation speed and heating bath temperature: fast turning for large jumps, slow turning for precise setting of the set values
- Accidental changing of the values can be prevented by the lock function
- Intuitive LED ring light system makes activated functions clearly visible even from a distance
- Easy adjustment of the immersion depth up to 155 mm and the inclination angle from 20° to 80°
- Standby function and residual heat warning at heating bath temperatures above 50 °C
- Hand lift model with transparent plastic coated G5 dry ice condenser
- The standby button stops all functions.

Learn about the differences between this configuration with a G3XL condenser in combination with a recirculating chiller.

Hei-VAP Core - Technical Data

Permissible ambient conditions 5 - 31 °C at 80 % rel. humidity 32 - 40 °C decreasing lineary up to max 50% rel. humidity Protection class DIN EN 60529 Lift Hand lift Height adjustment speed Height adjustment Drive brushless DC motor with electronic speed control Heating capacity 1,300 W Temp. range heating bath 20 - 210 °C Temperature accuracy bath ±1K Overheat protection bath cut-off at 5 °C over set temperature via separate PT 1000 Bath temperature setting 3.5" LCD Display Heating bath temperature control electronic / digital Secondary overtemp. cut off 250 °C
Lift Hand lift Height adjustment speed manual Height adjustment 155 mm Drive brushless DC motor with electronic speed control Heating capacity 1,300 W Temp. range heating bath 20 - 210 °C Temperature accuracy bath ±1K Overheat protection bath cut-off at 5 °C over set temperature via separate PT 1000 Bath temperature setting 3.5" LCD Display Heating bath temperature control electronic / digital
Height adjustment speed Height adjustment Drive brushless DC motor with electronic speed control Heating capacity 1,300 W Temp. range heating bath 20 - 210 °C Temperature accuracy bath ±1K Overheat protection bath cut-off at 5 °C over set temperature via separate PT 1000 Bath temperature setting 3.5" LCD Display Heating bath temperature control electronic / digital
Height adjustment Drive brushless DC motor with electronic speed control Heating capacity 1,300 W Temp. range heating bath 20 - 210 °C Temperature accuracy bath ±1K Overheat protection bath cut-off at 5 °C over set temperature via separate PT 1000 Bath temperature setting 3.5" LCD Display Heating bath temperature control electronic / digital
Drive brushless DC motor with electronic speed control Heating capacity 1,300 W Temp. range heating bath 20 - 210 °C Temperature accuracy bath ±1K Overheat protection bath cut-off at 5 °C over set temperature via separate PT 1000 Bath temperature setting 3.5" LCD Display Heating bath temperature control electronic / digital
Heating capacity Temp. range heating bath 20 - 210 °C Temperature accuracy bath ±1K Overheat protection bath cut-off at 5 °C over set temperature via separate PT 1000 Bath temperature setting 3.5" LCD Display Heating bath temperature control
Temp. range heating bath 20 - 210 °C Temperature accuracy bath 21K Overheat protection bath cut-off at 5 °C over set temperature via separate PT 1000 Bath temperature setting 3.5" LCD Display Heating bath temperature control electronic / digital
Temperature accuracy bath ±1K Overheat protection bath cut-off at 5 °C over set temperature via separate PT 1000 Bath temperature setting 3.5" LCD Display Heating bath temperature control electronic / digital
Overheat protection bath cut-off at 5 °C over set temperature via separate PT 1000 Bath temperature setting 3.5" LCD Display Heating bath temperature control electronic / digital
Separate PT 1000 Bath temperature setting 3.5" LCD Display Heating bath temperature control electronic / digital
Heating bath temperature control electronic / digital
Secondary overtemp. cut off 250 °C
<u> </u>
Material heating bath stainless steel V4A
Diameter heating bath 255 mm
Volume heating bath 4.5 l
Display vapor temperature -
Required accessories for display vapor - temperature
Integrated vacuum controller -
Timer -
Programmable ramps -
Supply Power 1,400 W
Weight without glassware assembly 15 kg

Premium Laboratory Equipment

Dimensions with glassware set G3 (w/d/h)	739 x 487 x 845 mm
Dimensions with glassware set G3 XL (w/d/h)	739 x 487 x 920 mm
Condensing surface	1,400 cm²
Condensing surface XL condenser	2,200 cm²
Max. size evaporating flask	51
Rotation speed range	10 - 280 rpm
Integrated Hei-CHILL controller	-
Vacuum program Dynamic AUTOaccurate requires AUTOaccurate sensor	_
Solvent libary	-