



designed for scientists

## Technical Data

Heat output [W]	1400
Heating temperature range [°C]	room temp. - 180
Heat control	Turning knob
Set temperature resolution [±K]	1
Controller oscillation (3 l water / 90 °C) [±K]	1
Absolute deviation/mean (3l water / 90 °C) [±K]	2
Controller oscillation (3l Silicone oil / 50mPas / 150°C) [±K]	2
Absolute deviation/mean (3 l Silicone oil / 50mPas/ 150°C) [±K]	4
Speed display	LCD
Filling volume max. [l]	4
Filling point min. [mm]	60
Material in contact with medium	stainless steel 1.4404
Fixed safety circuit [°C]	190
Adjustable safety circuit [°C]	50 - 190
Class designation acc. DIN 12876	II
Outer diameter [mm]	257
Inner diameter [mm]	225
Outer height [mm]	190
Inner height [mm]	130
Dimensions (W x H x D) [mm]	330 x 190 x 325
Weight [kg]	3.9
Permissible ambient temperature [°C]	5 - 40
Permissible relative humidity [%]	80
Protection class according to DIN EN 60529	IP 21
USB interface	yes
Voltage [V]	200 - 240 / 100 - 120
Frequency [Hz]	50/60
Power input [W]	1450
Power input standby [W]	3