

---

# General Specifications

---

## Specifications

Power Requirements: 100 VAC  $\pm$ 10%, 50/60 Hz, 120 VAC  $\pm$ 10%, 60 Hz, 230 VAC  $\pm$ 10%, 50/60 Hz

Small/medium unit: 3.4 A @ 120 VAC, 1.8 A @ 230 VAC

Dual unit: 6.8 A @ 120 VAC, 3.6 A @ 230 VAC

Ambient conditions: +16 to 40°C, up to 90% relative humidity, non-condensing

Temperature range: Ambient +7 to 85°C

Average uniformity:  $\pm$ 0.5°C at 55°C within the chamber;  $\pm$ 0.25°C at 55°C sample to sample

Heat-up time: 20 minutes from ambient to 65°C

Rotisserie speed: 5-15 rpm

Maximum altitude: 2000 m

Over-voltage category: II (IEC 664)

Pollution degree: 2 (IEC 664)

Exterior dimensions:

W x L x H (nominal)      Small: 18 x 16.5 x 17 inches (46 x 42 x 44 cm)  
Medium: 18 x 20 x 20.5 inches (46 x 51 x 53 cm)  
Dual: 18 x 20 x 41 inches (46 x 51 x 104 cm)

Weight:                      Small: 45 lbs (21 kg)  
Medium: 55 lbs (25 kg)  
Dual: 105 lbs (48 kg)



**Note: (230 VAC units only)**

CE products meet the relevant EC harmonized standards for safety (IEC1010-1/EN61010) and EMC (EN61326-1).