

---

## Performance Characteristics

Operating Range	50 to 225 °C	
Average Uniformity @ 200 °C	± 4.5 °C	
Resolution	1 °C	
Control Sensitivity	± 0.5 °C	
Recovery time @ 200 °C (door opened one minute)		
Model 625	2.0 minutes	
Model 637	4.0 minutes	
Model 650	4.0 minutes	
Rise Time to 225 °C		
Model 625	45 minutes	
Model 637	60 minutes	
Model 650	120 minutes	
Air Exchanges		
Model 625	24 per hour	
Model 637	16 per hour	
Model 650	12 per hour	
BTU/hour Output	@ 100 °C	@ 200 °C
Model 625	470	1325
Model 637	1040	2025
Model 650	1150	2040

---

## **Specifications**

### **Electrical Requirements**

Model 625	Cat. No. 13-247-625G	120 V, 50/60 Hz
	Cat. No. 13-247-626G	240 V, 50/60 Hz
Model 637	Cat. No. 13-247-637G	120 V, 50/60 Hz
	Cat. No. 13-247-638G	240 V, 50/60 Hz
Model 650	Cat. No. 13-247-650G	120 V, 50/60 Hz
	Cat. No. 13-247-651G	240 V, 50/60 Hz

### **Power Requirements**

Model 625	1300 W
Model 637	1300 W
Model 650	1300 W

### **Chamber Volumes**

Model 625	2.5 cu ft.
Model 637	3.8 cu ft.
Model 650	5.0 cu ft.

### **Chamber Dimensions (W x D x H)**

Model 625	18 x 18 x 13.5 in
Model 637	18 x 18 x 20 in
Model 650	18 x 18 x 26.5 in

---

---