

## Technical Data

Number of stirring positions	1
Stirring quantity max. per stirring position (H <sub>2</sub> O) [l]	20
Motor rating output [W]	9
Direction of rotation	right
Speed display set-value	LED
Speed display actual-value	LED
Speed adjustment	Turning knob
Speed range [rpm]	50 - 1500
Setting accuracy speed [rpm]	10
Stirring bar length [mm]	20 - 80
Self-heating of the set-up plate by max. stirring (RT:22°C/duration:1h) [K]	+13
Heat output [W]	600
Temperature display set-value	LED
Temperature display actual-value	LED
Temperature unit	°C
Heating temperature range [°C]	Room temp. + device self heating - 310
Heat control	Turning knob
Temperature setting range [°C]	0 - 310
Temperature setting resolution of heating plate [K]	1
Connection for ext. temperature sensor	PT1000, ETS-D5, ETS-D6
Heating rate medium [K/min]	6.5
Temperature setting resolution of medium [K]	1
Adjustable safety circuit [°C]	50 - 360
Set-up plate material	Aluminium alloy
Set-up plate dimensions [mm]	Ø 135
Sensor in medium detection (Error 5)	yes
Temperature measure range PT1000 [°C]	-20 - 310
Speed deviation (no load, nominal voltage, at 1500rpm + 25 °C) [%]	±2
Heating rate (1l H <sub>2</sub> O in H1500) [K/min]	6.5
Heat control accuracy of heating plate (at 100°C) [K]	±5
Heat control accuracy with ext. PT1000 (500ml H <sub>2</sub> O in 600ml beaker, 40mm stirring bar, 600rpm, 50°C) [K]	±1
Heat control accuracy with ETS-D5 (500ml H <sub>2</sub> O in 600ml beaker, 40mm stirring bar, 600rpm, 50°C) [K]	±0.5
Heat control accuracy with ETS-D6 (500ml H <sub>2</sub> O in 600ml beaker, 40mm stirring bar, 600rpm, 50°C) [K]	±0.2
Dimensions (W x H x D) [mm]	160 x 85 x 270
Weight [kg]	2.4
Permissible ambient temperature [°C]	5 - 40
Permissible relative humidity [%]	80
Protection class according to DIN EN 60529	IP 42
RS 232 interface	yes
USB interface	yes
Voltage [V]	115
Frequency [Hz]	50/60
Power input [W]	650
Power input standby [W]	1.6