

Acid-Resistant Refrigerated CentriVap Centrifugal Vacuum Concentrator



View online: <https://www.labconco.com/product/acid-resistant-refrigerated-centrivap-centrifugal-vacuum-concentrator-8/589>

Overview



Using centrifugal force, vacuum and controlled heat, the Acid-Resistant CentriVap Vacuum Concentrator rapidly concentrates multiple small samples containing chemicals such as 0.1 to 1% TFA, hydrochloric acid, acetic acid, hydrobromic acid, ammonium hydroxide and sodium hydroxide. Components in the vapor path are constructed of corrosion-resistant materials for long life.

Catalog Number: 7310042

Specifications

- **Weight:** 108.0 lbs
- **Weight metric:** 49.0 kg
- **Dimensions:** 14.3" w x 21.7" d x 16.6" h
- **Dimensions metric:** 36.3 x 55.1 x 42.2 cm
- **Region:** U.S. and Canada
- **300-Watt Heat Boost:** Not Included
- **CentriVap Optional Accessories:** CentriZap Strobe Light, Rotors, Vacuum Controller, Laboratory Carts
- **CentriVap Required Accessories:** Acid Resistant Rotor, Diaphragm or Rotary Vane Vacuum Pump, Sample Tubes
- **Conformance:** ETL, ETL
- **Lid Type:** Glass
- **Receptacle and Plug Type:** North America, 230 volts
- **Style:** Benchtop
- **Type/Application:** Acids, Temperature-Sensitive Samples

Description

Compliance

- UL 3101-1/61010-1
- CAN/CSA C22.2 No. 110.1 (115 V models)
- CE Conformity Marking (230 V models)

Features

- Brushed stainless steel and glacier white, epoxy-coated steel exterior with blue accents.
- Glass lid.
- Lid latch with safety sensor.
- Phenol-free lid gasket.
- PTFE-coated aluminum chamber with Hastelloy shaft.
- 300-watt heater.
- Microprocessor-controlled programming for run time from 1 to 999 minutes, heat from OFF to HI (100° C) in one degree increments, and heat time from 1 to 999 minutes. Memory stores 1 to 9 programs.
- LCD for display of program number, actual and set point temperature, heater time remaining, and run time remaining.
- Control panel with RUN/STOP button, PREHEAT button, set point SELECT button, increase/decrease buttons, and 3 Quick-Start buttons.
- Centrifugal motion is provided by a brushless motor capable of achieving up to 1725 rpm.
- Quick-Stop System to stop vacuum pump, open valve to bleed air into the chamber and stop the rotor within seconds after time expires or RUN/STOP button is pressed.
- Automatic vacuum release valve.
- Built-in vacuum delay allows rotor to achieve speed before applying vacuum.
- Audible alarm to signal completion of set point run time.
- 1/2" OD aluminum hose fitting for connection to vacuum tubing. Vacuum pump is not included.
- Vacuum port with quick disconnect fitting for 1/4" ID tubing.
- 115 volt models have a 115 volt electrical receptacle on the back to connect accessory vacuum pump to the system.
- 230 volt models have a reverse IEC electrical receptacle on the back to connect accessory vacuum pump to the system.
- 115 volt models have a 6.5-foot, 3-wire cord with NEMA 5-15 plug.
- 230 volt models have an 8-foot cord with NEMA 6-15 plug.
- Overall dimensions with closed lid: 14.7" wide x 19.3" deep x 11.7" high (37.3 x 49.0 x 29.7 cm).
- Actual weight 45 lbs. (20 kg). Shipping weight 65 lbs. (29 kg).

Options

- International electrical configuration

Required Accessories

- Diaphragm or Rotary Vane Vacuum Pump
- CentriVap Cold Trap if using a Rotary Vane Vacuum Pump
- Rotors
- Sample tubes

Optional Accessories

- CentriZap Strobe Light

- Vacuum Controller
- Laboratory Carts

For Product Assistance



[Andy Miller](#)
Senior Sales Representative



[Vivian Goldman](#)
Customer Service
Representative



Labconco Corporation
8811 Prospect Avenue
Kansas City, MO 64132-2696
Phone: (816) 333-8811

