

LABNET INTERNATIONAL, INC.

ACCUPLATE™

HOTPLATES, STIRRERS
AND HOTPLATE STIRRERS

Labnet
Labnet International, Inc.



- Precise liquid temperatures and stirring speeds
- Digital display and safety indicators
- Angled front panel and large knobs
- Optional external temperature controller



ACCUPATE™

HOTPLATES, STIRRERS AND HOTPLATE STIRRERS

Labnet's AccuPlate digital hot plates and stirrers are versatile, powerful and easy to use. Every unit is built for consistent performance and long term reliability. With 3 models to choose from, there is an AccuPlate to meet your lab's needs.

Ceramic Advantage

Each AccuPlate is equipped with a Pyroceram® ceramic top plate which offers significant advantages over comparable metal topped units. This ceramic material is extremely durable, easy to clean and is highly resistant to chemical attack. In addition, ceramic plates can reach higher temperatures (rated to 550°C) than metal topped units and the white color makes it easy to view color changes in applications such as titrations.

Temperature Control

The AccuPlate Hotplate and Hotplate Stirrer models incorporate a powerful heating element positioned directly beneath the ceramic top plate. This provides optimal heat transfer to the plate and sample while minimizing heat transfer to the electronics and housing. Temperature is set using the large control knob and easy to read LED display. An optional temperature probe allows closed-loop temperature control for enhanced temperature accuracy. Accuracy is within $\pm 2^{\circ}\text{C}$ of the set temperature (when using the optional temperature probe).



Stirring Performance

The AccuPlate Stirrer and Hotplate Stirrer utilize a powerful motor drive system paired with strong permanent magnets to ensure a consistent connection to the stir bar. The stirring speed is accurate to within $\pm 5\%$ of the set speed. The control software is designed to minimize stir bar decoupling by regulating the acceleration rate of the motor. This allows for a range of sample viscosities to be stirred.

Intelligent Design

Bright LED displays for speed and temperature are easy to read and large control knobs make parameter setting simple. The angled faceplate makes the display easier to read and prevents liquids from damaging the electronics. A durable cast aluminum housing incorporates a channel to direct liquids to the sides of the unit in the event of an accidental spill. The raised underside of the unit is vented to keep the internal components cool, even during extended operation.

Safety Features

The AccuPlate Hotplate and Hotplate Stirrer models feature a bright red "Hot Top" indicator to alert users that the ceramic top is too hot to touch – even if the heater is off, the light will remain on until the top has cooled sufficiently to handle. The software also incorporates a number of error codes to detect a range of abnormal performance conditions. In the event of an atypical operating condition (i.e. running the unit without proper ventilation), the AccuPlate will shut down for safety. A thermal fuse is also incorporated into the electronics to prevent over-heating in the event of a problem with the primary temperature controller.



ACCUPATE™

Specifications and Ordering Information

	AccuPlate Hotplate	AccuPlate Stirrer	AccuPlate Hotplate Stirrer
Catalog No.	D0400 / D0400-230V	D0410 / D0410-230V	D0420 / D0420-230V
Temperature Range	5° - 550°C (41°-1022°F)	N/A	5° - 550°C (41°-1022°F)
Temperature Accuracy	±2°C	N/A	±2°C
Speed Range	N/A	60-1150RPM	60-1150-RPM
Speed Accuracy	N/A	±5%	±5%
Top Plate Material	Ceramic	Ceramic	Ceramic
Top Plate Size	12.7 x 17.8cm (5" x 7")	12.7 x 17.8cm (5" x 7")	12.7 x 17.8cm (5" x 7")
Product Dimensions (WxDxH)	7.75 x 11 x 4.25" (19.7 x 28 x 10.8cm)	7.75 x 11 x 4.25" (19.7 x 28 x 10.8cm)	7.75 x 11 x 4.25" (19.7 x 28 x 10.8cm)
Weight	2.7kg (6.0lbs.)	3.2kg (7.0lbs.)	3.2kg (7.0lbs.)
Electrical	120 or 230V, 50/60Hz	120 or 230V, 50/60Hz	120 or 230V, 50/60Hz

ORDERING INFORMATION

Catalog No. Description

D0400	AccuPlate Hotplate, 5"x7" Ceramic top, 120V, US Cord
D0400-230V	AccuPlate Hotplate, 5"x7" Ceramic top, 230V, EU and UK Cords
D0410	AccuPlate Stirrer, 5"x7" Ceramic top, 120V, US Cord
D0410-230V	AccuPlate Stirrer, 5"x7" Ceramic top, 230V, EU and UK Cords
D0420	AccuPlate Hotplate Stirrer, 5"x7" Ceramic top, 120V, US Cord
D0420-230V	AccuPlate Hotplate Stirrer, 5"x7" Ceramic top, 230V, EU and UK Cords
D0461	Kit includes D0462, D0466 and Stir Bar retriever
D0462	External Temperature Probe (for D0400 and D0420)
D0463	PTFE coated magnetic stir bar (1 x 2.5cm)
D0464	Boss Head clamp – for holding D0465 at a 90° angle from D0466
D0465	Temperature probe (D0462) holding rod
D0466	Vertical Support Rod (two 22.8cm rods which can be connected)

