









Rotor A-4-81 with conical tubes














		Max. g-force:	3,220 x g
Rotor A-4-81 Swing-bucket rotor with 4 conical tubes	Bucket for 7 x 50 mL conical tubes	Max. speed:	4,000 rpm
		Max. load:	7 x 75 g

Tube	Tube Capacity Tubes per adapter/ rotor	Adapter Order no. (international)	Bottom shape Tube diameter Max. tube length	Max. g-force Max. speed Centrifugation radius
	Conical tube 15 mL 7/28	 5820 718.005	conical Ø 17.5 mm 120 mm	3,184 x g 4,000 rpm 17.8 cm
	Conical tube 50 mL 7/28	-	conical Ø 30 mm 117 mm	3,220 x g 4,000 rpm 18.0 cm

Rotor A-4-81 with MTP/Flex bucket

		Max. g-force:	2,900 x g
Rotor A-4-81 Swing-bucket rotor with 4 MTP/Flex buckets	MTP/Flex buckets	Max. speed:	4,000 rpm
		Max. load per bucket:	380 g

Tube	Plate Capacity Plates, rack or glass slides per adapter/ rotor	Adapter Order no. (international)	Bottom shape Tube diameter Max. loading height	Max. g-force Max. speed Centrifugation radius
	Micro test plate 96/384 wells 4/16	-	flat - 60 mm	2,900 x g 4,000 rpm 16.3 cm

Tube	Plate Capacity Plates, rack or glass slides per adapter/ rotor	Adapter Order no. (international)	Bottom shape Tube diameter Max. loadingheight	Max. g-force Max. speed Centrifugation radius
	Deepwell plate 96 wells 1/4	-	flat - 60 mm	2,900 x g 4,000 rpm 16.3 cm
	Cell culture plate 24 wells 2/8	-	flat - 60 mm	2,900 x g 4,000 rpm 16.3 cm
	Kit 1/4	-	flat - 60 mm	2,900 x g 4,000 rpm 16.3 cm
	Tube in IsoRack 24 x 0.5 mL 1/4	 5825 708.008	flat Ø 6 mm 60 mm	2,700 x g 4,000 rpm 15.0 cm
	Tube in IsoRack 24 x 1.5/2 mL 1/4	 5825 709.004	flat Ø 11 mm 60 mm	2,600 x g 4,000 rpm 14.6 cm
	384-well PCR plate 1/4	 5825 713.001	flat - 60 mm	2,700 x g 4,000 rpm 15.8 cm
	96-well PCR plate 1/4	 5825 711.009	flat - 60 mm	2,600 x g 4,000 rpm 16.1 cm
Slides	CombiSlide 12/48 or 8/32	  5825 706.005	flat - 60 mm	1,000 x g 2,372 rpm 15.9 cm