


8 Technical data

8.1 Specifications

 The use of baffled flasks will significantly reduce maximum speed for any shaker.

These specifications assume a maximum load of 15.5 kg (34 lb), including platforms, clamps, glassware, and contents.

8.1.1 Shaking

Speed	<ul style="list-style-type: none"> • 25 – 400 rpm
Control accuracy	<ul style="list-style-type: none"> • ± 1 rpm
Stroke	<ul style="list-style-type: none"> • 1.9 cm (3/4 in) • 2.54 cm (1 in)
Indication	<ul style="list-style-type: none"> • Displayed in 1 rpm increments
Alarm signal	<ul style="list-style-type: none"> • Visible and audible alarm when speed deviates ± 5 rpm from setpoint
Drive mechanism	Triple-eccentric counterbalanced drive with nine permanently lubricated ball bearings
Safety	Drive Interrupt shuts off power to Shaker when door opens. Acceleration/deceleration circuit prevents sudden starts and stops, minimizing both splashing and mechanical damage. Independent mechanical sensing switch also shuts the motor off in unbalanced condition.

8.1.2 Temperature control

Heaters	Long-life, low-watt density resistance-type heater with high temperature thermostat
Control accuracy	<ul style="list-style-type: none"> • ± 0.1 °C at 37°C • ± 0.5 °C over the remaining range
Temperature range (42)	<ul style="list-style-type: none"> • 10 °C above ambient temperature to 80 °C
Temperature range (42R)	<ul style="list-style-type: none"> • 20 °C below ambient temperature (minimum 4 °C) to 80 °C
Alarm signal	<ul style="list-style-type: none"> • Visible and audible alarm when temperature deviates ± 1 °C from setpoint

Technical data

New Brunswick™ Innova®42/42R Shaker
English (EN)

8.1.3 Power supply

<ul style="list-style-type: none"> • 100 V ±10 %, 50/60 Hz • 120 V ±10 %, 60 Hz • 230 V ±10 %, 50 Hz 	1500 VA
Overvoltage category	II

8.1.4 Dimensions

	Width	Depth	Height
Space requirements	84 cm (33 in)	85 cm (33.5 in)	84 cm (33 in)
Dimensions	63.5 cm (25 in)	74.5 cm (29.3 in)	81.8 cm (32.2 in)
Chamber dimensions	51.7 cm (20.4 in)	51.5 cm (20.3 in)	47.7 cm (18.8 in)
Platform dimensions	46 cm (18 in)	46 cm (18 in)	

8.1.5 Weight

42	98 kg (216 lb)
42R	121 kg (266 lb)

8.1.6 Ambient conditions

Ambience	Only for use indoors
Ambient temperature	10 °C – 35 °C
Relative humidity	20 % – 80 % (non-condensing)
Altitude	Up to 2000 m
Pollution degree	2

8.1.7 CE directives and standards

See declaration of conformity.

8.1.8 Compliance and certifications

UL 61010-1; UL 61010-2-010; UL 61010-2-011; UL 61010-2-051.
CAN/CSA C22.2 No. 61010-1-12; CAN/CSA C22.2 No. 61010-2-010
CAN/CSA C22.2 No. 61010-2-011; CAN/CSA C22.2 No. 61010-2-051.

8.1.9 Features

Alarms	Visible and audible warning indication when speed deviates more than 5 rpm or temperature more than 1 °C from setpoints, and when timer has expired. Audible alarm can be muted.
Display	240 x 128 backlit
RS-232	Remote control, remote monitoring, remote data logging.
Setpoint retention	All setpoints and operating status are retained in non-volatile memory.
Automatic restart	Automatic restart after power is restored, indicated by flashing display.

8.1.10 Fuses

Next to Outlet:

- 0.5 A glass tube, slow-blowing, for 230 V operation only
- 0.75 A glass tube, slow-blowing, for 120 V operation only
- 1.0 A glass tube, slow-blowing, for 100 V operation only

8.2 Load/speed graphs

In the following graphs, 20 % and 50 % indicate level to which flasks were filled. These are sample load/speed runs provided for your information.