

Technical Information

Performance Specifications

Working Temperature: Ambient +5°C to 100°C (ambient +10° to 212°F)
60°C (140°F) without cover

Temperature Uniformity: ±0.2°C @ 37°C (±0.4°F @ 98.6°F)

Temperature Stability: ±0.1°C (±0.2°F)

Reservoir Size	Reservoir Dimensions (L x W x D)	Heater Wattage	Electrical Requirements	
			120 V, 60 Hz	220-240V, 50/60Hz
2 liter	3.9 x 4.3 x 6" 9.9 x 10.9 x 15.2 cm	120	WB02, WB02**1* 1.1 A	WB02, WB02**2* 0.5 A
2 liter shallow	5 x 10.8 x 2.6" 12.7 x 27.4 x 6.5 cm	360	WB02S, WB02S**1* 3.3 A	WB02S, WB02S**2* 1.6 A
5 liter	5 x 10.8 x 6" 12.7 x 27.4 x 15.2 cm	360	WB05, WB05**1* 3.3 A	WB05, WB05**2* 1.6 A
10 liter	10.6 x 11.6 x 6" 26.9 x 29.5 x 15.2 cm	1000	WB10, WB10**1* 8.6 A	WB10, WB10**2* 4.5 A
20 liter	9.5 x 17 x 6" 24.1 x 43.2 x 15.2 cm	1400	WB20, WB20**1* 12.0 A	WB20, WB20**2* 6.0 A
28 liter	9.5 x 17 x 8" 24.1 x 43.2 x 20.3 cm	1400	WB28, WB28**1* 12.0 A	WB28, WB28**2* 6.0 A

Environmental Conditions Indoor use only
Maximum Altitude: 2000 meter
Operating Ambient: 5° to 40°C (41° to 104°F)
Relative Humidity: 80%, non-condensing
Installation Category: II
Pollution Degree: 2