

ADVANCED DRY BLOCK HEATER SPECIFICATIONS - 120 VOLT

	1 Block	2 Block	3 Block	4 Block	6 Block	2 Block with Lid
Dimensions (L x W x H):	12.4 x 8 x 3.5" (31.5 x 20.3 x 8.9cm)	15.4 x 8 x 3.5" (39.1 x 20.3 x 8.9cm)	18.4 x 8 x 3.5" (46.7 x 20.3 x 8.9cm)	16.9 x 8 x 3.5" (42.9 x 20.3 x 8.9cm)	20.9 x 8 x 3.5" (53.1 x 20.3 x 8.9cm)	15.4 x 8 x 7" (39.1 x 20.3 x 17.8cm)
Electrical 120V 50/60 Hz:	0.9 amps, 110 watts	1.7 amps, 210 watts	1.7 amps, 210 watts	2.6 amps, 310 watts	3.4 amps, 410 watts	3.0 amps, 400 watts
Fuses:	5mm x 20mm, 5 amp quick acting					
Temperature range:	ambient +5°C to 120°C					ambient +5°C to 100°C
Stability @ 37°C:	+/-0.1°C					
Uniformity w/in the block @ 37°C:			+/-0.1°C			+/-0.1°C
Uniformity across similar blocks @ 37°C:	N/A	+/-0.1°C	+/-0.15°C	+/-0.2°C	+/-0.3°C	+/-0.1°C
Stability @ 60°C:	+/-0.4°C					
Uniformity w/in the block @ 60°C:			+/-0.4°C			
Uniformity across similar blocks @ 60°C:	N/A	+/-0.5°C	+/-0.7°C	+/-0.8°C	+/-1°C	+/-0.5°C
Heat-up time to 100 °C:	45 min.	50 min.	55 min.	60 min.	65 min.	50 min.
Controls:	see page 8					
Ship weight:	5.8lbs (2.6kg)	6.4lbs (2.9kg)	8lbs (3.6kg)	8.5lbs (3.9kg)	10lbs (4.5kg)	7lbs (3.2kg)