



Cabinets shown: 23.3 cu. ft. single door (ULT2304) lab freezer and 51.1 cu. ft. double door (ULT5030) lab freezer

Thermo Scientific Revco High-Performance -20°C Freezers with Manual Defrost

Model No.	Cu.Ft. (L)	Voltage (Hz)	Certification	Plug	Cabinet	Door	Adjustable Shelves	Int. Dimensions* H x D x W inches (mm)	Ext. Dimensions* H x D x W inches (mm)	Ship Weight lb (kg)
UGL2320A	23.3	115 (60)	UL	NEMA 5-15	upright	single,	4	58.0 x 29.0 x 24.0	79.2 x 37.2 x 28.0	425
UGL2320D	(659)	208/230 (60)	UL	NEMA 6-16		solid		(1473 x 737 x 610)	(2012 x 945 x 711)	(193)
UGL2320V		230 (50)	CE	European						
UGL2320W‡		230 (50)	CE	U.K.						
UGL3020A	29.2	115 (60)	UL	NEMA 5-15	upright	single	4	58.0 x 29.0 x 30.0	79.2 x 37.2 x 34.0	445
UGL3020D	(826)	208/230 (60)	UL	NEMA 6-16				(1473 x 737 x 762)	(2012 x 945 x 864)	(197)
UGL3020V		230 (50)	CE	European						

* Published interior volumes are nominal; useable cu.ft. (L) capacities may be offset by shelves, drawers, blower coils, or cabinet protrusions. For specific cabinet dimensions and allowances, or for verification of clearance tolerances, contact our sales representative. Product performance may be affected by ambient temperature conditions, humidity conditions, sample loading preferences, and frequency of door openings. Contact our sales representative for specific inquiries regarding your application.

‡ Due to differences in building wiring regulations in Australia and New Zealand, the current draw for the W-voltage units rated less than 10A may utilize a 10A circuit breaker. This rating only applies to Australia and New Zealand. Confirm the amperage rating on the data plate. Contact your local sales representative for more information.