

ADVANCED DRY BLOCK HEATER SPECIFICATIONS - 120 VOLT

	1 Block	2 Block	4 Block	6 Block	2 Block with Lid
Dimensions (L x W x H):	10.6 x 7.7 x 4.6" (26.9 x 19.6 x 11.7cm)	13.7 x 7.7 x 4.6" (34.8 x 19.6 x 11.7cm)	16.7 x 7.9 x 4.1" (42.4 x 20.1 x 10.4cm)	20.7 x 7.9 x 4.1" (52.6 x 20.1 x 10.4cm)	13.7 x 7.7 x 7.4" (34.8 x 19.6 x 18.8cm)
Electrical 120V 50/60 Hz:	0.9 amps, 100 watts	1.8 amps, 190 watts	2.7 amps, 290 watts	3.4 amps, 360 watts	3.0 amps, 320 watts
Fuses:	5mm x 20mm, 5 amp quick acting				
Temperature range:	ambient +5°C to 120°C				ambient +5°C to 100°C
Stability @ 37°C:	+/-0.1°C				
Uniformity w/in the block @ 37°C:	+/-0.1°C				
Uniformity across similar blocks @ 37°C:	N/A	+/-0.1°C	+/-0.2°C	+/-0.3°C	+/-0.1°C
Stability @ 60°C:	+/-0.4°C				
Uniformity w/in the block @ 60°C:	+/-0.4°C				
Uniformity across similar blocks @ 60°C:	N/A	+/-0.5°C	+/-0.8°C	+/-1°C	+/-0.5°C
Heat-up time to 100°C:	45 min.	50 min.	70 min.	75 min.	50 min.
Controls:	see page 8				
Ship weight:	5lbs (2.3kg)	5.7lbs (2.6kg)	8.8lbs (4kg)	10lbs (4.5kg)	8.7lbs (3.9kg)