## VWR® STANDARD SERIES FREE STANDING UNDERCOUNTER REFRIGERATOR AND FREEZER

These Standard Series Undercounter Refrigerators and Freezers are designed specifically for general-purpose applications where precise temperature control, maintenance and alarms are not necessary.

Environmentally friendly, natural hydrocarbon (HC) refrigerants (not containing hydrofluorocarbons) vastly reduce global-warming potential (GWP) while meeting new EPA/SNAP mandates and UL, ASHRAE compliance guidelines.

Warning: Units marked as 'freestanding' are not designed for built-in and/or enclosed installations. Improper installation will void the warranty and will lead to temperature maintenance issues, overheating and possible failure.

- Keyed door locks
- Probe access port
- Manual defrost

Certifications: UL/C-UL Listed.



Description	Volume, L (cu. ft.)	Electrical	Exterior Dimensions, W x D x H, in.	Door Type	No. of Shelves	Temperature Range	Cat. No.
Freestanding Refrigerator	130 (5)	115 V, 60 Hz, 0.90 A	20¼ × 22 × 31½	1 Solid Swing	(2 Adjustable/1 Fixed)	1 to 10°C	10819-650
Freestanding Freezer	113 (4)	115 V, 60 Hz, 0.90 A	20¼ × 215/8 × 31½	1 Solid Swing	2 Fixed	-25 to -15°C	10819-894

## VWR® CRITICAL STORAGE UNDERCOUNTER LABORATORY REFRIGERATOR AND FREEZER, MANUAL DEFROST

These units are designed to meet the demanding standards of clinical, life science, pharmaceutical, biotechnology and industrial applications. They offer exceptional temperature control and uniformity via a door-mounted microprocessor controller and interior forced air circulation.

A built-in front-breather condenser allows units to be placed under benches or countertops and requires no additional clearance from the top, back or sides of the cabinet. These compact units can also be left free standing, placed side by side or securely stacked to create a combination refrigerator/freezer. A keyed door ensures safe and secure storage within each unit. The refrigerator is equipped with adjustable wire shelves; the freezer is equipped with fixed evaporator shelves. Both units feature a right-hinged door swing and a rounded door profile and handle.

- Optimal performance in clinical, life science, pharma, biotechnology and industrial applications
- Exceptional temperature control and uniformity
- Microprocessor control with user-programmable functions and features
- Built-in front-breather condenser

**Certifications:** Both models meet JCAHO standards for controlling medication access.



Description	Volume, L (cu. ft.)	No. of Shelves	Temperature Range	Cat. No.
Refrigerator	173 (6)	3	2 to 8°C	89031-974
Manual Defrost Freezer	153 (5.4)	2	−25 to −15°C	89031-976