




## Symbols and conventions

The following chart is an illustrated glossary of the symbols that are used in this manual.

	<b>CAUTION</b> This symbol indicates a potential risk and alerts you to proceed with caution.
	<b>CAUTION</b> This symbol indicates the presence of high voltage and warns the user to proceed with caution.
	<b>CAUTION</b> This symbol indicates a risk of fingers crush hazard between moving platform and housing.

## Product Specifications

The casing of rocker is made of plastic and steel plate varnished with high resistant polyurethane lacquer.

Specifications	VWR Rocking Platform 115V	VWR Rocking Platform 230V
Electrical	115V $\pm$ 10%, 50/60Hz, 0.3A	230V $\pm$ 10%, 50/60Hz, 0.15A
Motor power	6 W	6 W
Fuses	2 x 1AT	2 x 1AT
Speed	10 - 120 Rocks Per Minute	10 - 120 Rocks Per Minute
Tilt angle	$\pm$ 2.5° - 20° from horizontal (in 2.5° steps)	$\pm$ 2.5° - 20° from horizontal (in 2.5° steps)
Timer	10 - 120 min, HOLD function	10 - 120 min, HOLD function
Maximum load	5 kg	5 kg
Dimensions W x D x H	360 x 360 x 170 mm (single platf.) 360 x 360 x 260 mm (double platf.)	360 x 360 x 170 mm (single platf.) 360 x 360 x 260 mm (double platf.)
Platform dimensions W x D	360 x 280 mm	360 x 280 mm
Weight	6.5 kg (single platform) 7.8 kg (double platform)	6.5 kg (single platform) 7.8 kg (double platform)
Ambient conditions	-10°C to 70°C, up to 85% RH, non-condensing	-10°C to 70°C, up to 85% RH, non-condensing