

16,800  
RCF

## MC-24 Touch™ High Speed Microcentrifuge



CE



**Touch Control**



**Quiet Operation**



**High Speed**

## MC-24™ Touch High Speed Microcentrifuge

- + Full color touch screen
- + mySpin™ 1 button program recall
- + COMBI-Rotor™ accepts tubes and strips
- + Compact design, 9 x 12 x 7.75 in.
- + Unique air-flow system, keeps samples cool



**Unique COMBI-Rotor™**  
Accepts tubes and strips



**Full-color Touch Screen**

Benchmark's MC-24 Touch is the first microcentrifuge in its class with the convenience of touch pad control. In addition, this model comes complete with a unique COMBI-Rotor™ that accepts both standard microtubes and PCR strips, making this the ideal microcentrifuge for any microbiology laboratory.

The large, color touch screen shows actual speed (in rpm or rcf) along with set and remaining time. Up to 9 speed/time profiles can be stored in memory and the home screen displays a "mySpin" icon for instant recall of a designated favorite profile.

Supplied with Benchmark's unique COMBI-Rotor™, the MC-24 Touch will accept 24x1.5/2.0ml tubes and 2 strips of 0.2ml tubes (16x0.2ml) without requiring separate adapters. Samples are kept cool, even during extended runs at the maximum speed setting by a proprietary air flow system that moves air evenly and quietly throughout the chamber.

The MC-24 Touch is cold room safe and carries a 2 year warranty.

### Technical Data:

Speed Range:	<b>200 to 13,500 rpm (up to 16,800xg)</b>
Capacity:	<b>24 x 1.5/2.0ml 2 x PCR Strips (16 x 0.2ml)</b>
Speed Increment:	<b>100 rpm or 100 rcf</b>
Timer:	<b>20 sec. to 99 min. / cont.</b>
Momentary:	<b>Yes</b>
Dimensions: (W x D x H)	<b>9 x 12 x 7.75 in. 23 x 30.5 x 19.7cm</b>
Weight:	<b>14 lbs / 6.4 kg</b>
Electrical:	<b>115 or 230V, 50-60 Hz, 100W</b>
Warranty:	<b>2 years</b>

### Ordering Information:

Item No.	Description:
C2417*	MC-24 Touch Microcentrifuge with 24 place COMBI-Rotor
C1008-A5-6	Optional adapters for 0.5ml tubes in standard rotor, 6/pk
C2417-ROT5	Optional rotor, 8x 5ml (13,500rpm)
C2417-5-ADP	Optional adapters for 2ml cryovials in 8x5ml rotor, 8/pk

\*115V with US plug. For 230V (EU plug), please add (-E).