

# Vortemp 1550<sup>™</sup> Shaking Incubator

- Shake and incubate samples simultaneously
- Supplied with interchangelable platforms for 15 and 50mL tubes
- Broad temperature and speed range
- Intelligent control with digital LED display

### **Ordering Information**

Description
<b>Vortemp 1550</b> Shaking incubator for 15 and 50mL tubes, 120V
Individual adapters for 0.5/0.6mL tubes, pk/6
Individual adapters for 0.4mL tubes, pk/6
Individual adapters form 0.2mL tubes, pk/6

<sup>\*</sup>To order 230V units add -230V to the end of the catalog number. 230V units include EU and UK cords.



Temp Range Temp Accuracy Speed range Motion/orbit Timer Capacity

Dimensions

Weight

Ambient +5° to 99°C ±0.5°C

200 - 900 rpm Circular/3mm

1 - 99 min or continuous 18 x 15mL tubes or

8 x 50mL tubes 26 x 31 x 31cm/ 10.2 x 12.2 x 12.2 in

26.6 lb/12 kg





## Mini Incubator





#### Specifications

Temp Range Capacity Controls Exterior dims

Interior dims

Weight

Ambient +5° to 60°C 9.2 liters/0.375 cu ft Analog 28.5 x 28 x 33.5 cm/ 11.2 x 11 x 13.2 in 12 x 20 x 20 cm/ 9 x 7.9 x 7.9 in 18.4 lb/8.3 kg

- Ideal for small laboratories and classrooms
- Broad temperature range
- Rear cord port allows for use of small mixers inside
- Includes one shelf, which can be placed at two points within the corrosion resistant chamber

### Ordering Information

Cat#	Description
I5110A*	Mini Incubator, 120V
I5110-MLR*	Mini Incubator with Mini LabRoller and rotisseries for 1.5, 15 and 50mL tubes
I5110-SHELF	Additional shelf, 22 x 18 cm
W0020-110C	Non-toxic safety thermometer for -20° to 110°C, with 1 resolution, 305mm long, 76mm immersion

 $^*$ To order 230V units add -230V to the end of the catalog number, Specify cord type by adding -EU or -UK